REMARKS

Claim 1 remains in this application. Claim 1 has been amended. Claims 2 and 3 have been added. Reconsideration of this application in view of the amendments noted is respectfully requested.

Claim 1 was rejected under 35 USC Section 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention. Specifically, the examiner stated that the phrases "such as" in line 3, "air bags air spring" in line 3, "air bags or other air suspension means" in line 16, and "'encastre'" in line 20 are unclear and therefore render claim 1 indefinite. Claim 1 has been amended to overcome these rejections. The phrase "such as" has been eliminated and "air bags air spring" now reads --air bags--. Further, "air bags or other air suspension means" now reads --air bags--. Moreover, "tending towards 'encastre' at those one ends" now reads --tending towards being fixed at their pivotally connected ends by the anti-roll means--. This specifically states the meaning of 'encastre.' Applicant submits that claim 1 as amended is no longer indefinite and therefore respectfully requests that the Section 112 rejection be withdrawn.

Applicant has also made other amendments to claim 1 to make certain features of the claim more clear. Also, Applicant has added claims 2 and 3 to further define the anti-roll means introduced in claim 1. Support for these claims is found in the specification at page 9, lines 17 – 19 and page 10, lines 18 – 25.

Claim 1 was also rejected under 35 USC Section 103(a) as being unpatentable over McJunkin, Jr. (U.S.P.N. 3,711,079, hereinafter "McJunkin") in view of Wilson (U.S.P.N. 5,938,221, hereinafter "Wilson"). Applicant respectfully traverses this rejection. The present invention as found in the amended claims is directed to an air suspension anti-roll stabilization system in which an anti-roll means is connected rigidly to a pair of longitudinal leaf spring suspension arms upon which the air bags are mounted such that the longitudinal suspension arms act as beams which are pivotally mounted at

their one ends to the frame or chassis of the vehicle during normal vehicle motion and which are caused by the anti-roll means to act as beams which are fixed or tending towards being fixed at their pivotally connected ends during roll motion of the vehicle. This adds torsional stiffness to the suspension arms close to the pivot points to convert the arms from being pin-jointed to fixed-ended (encastre) beams during roll. This provides the advantage that the suspension system yields good ride quality under normal straight line vehicle motion but resists rolling of the vehicle on cornering (roll).

To particularize, see Figure 7C of the present application, where the torque created by the torsional stiffness mentioned above generates opposed moments C and D that reduce the spring deflection as would occur with a fixed ended beam, rather than in Figure 7B where a pin-jointed beam bending moment is shown. This ability to increase the bending moment stiffness of the leaf spring arm during roll of the vehicle, as a result of the suspension which is the subject of the present application, creates a vastly superior air suspension system, in that the geometry of the inventive system provides a much softer ride under normal straight ride conditions and high stability under dynamic roll (cornering) conditions.

In contrast to the present invention, the stabilizing bar taught by McJunkin is a generally U-shaped bar (22, 23, 33) of which a central portion (33) supplies a torque to resist roll of the vehicle (column 3, lines 13 to 23). The central portion (33) of the bar is positioned parallel to and adjacent the vehicle axle being secured through rearwardly directed legs (22, 23) which are secured to respective suspension arms (12, 13) extending in the longitudinal directions of said arms. It should be noted that the primary function of the stabilizing bar (22, 23, 33) is to dampen any undesirable deflections of the suspension arms through the resistance to deflection of said arms (22, 23) of the bar in the longitudinal directions of the suspension arms (12, 13) (column 2, line 64 through column 4, line 6)

In McJunkin, under vehicle roll conditions where the suspension arms (12, 13) are caused to deflect in opposite directions, it can be seen that the central portion (33) of the stabilizing bar adds transverse, torsional stiffness to the suspension arms at or close to the

connection points (36, 37) adjacent to the axle rather than to the connection points (34, 35) adjacent the connection points by which the suspension arms are pivotally mounted to the vehicle frame or chassis. Consequently, the anti-roll means does not act on the suspension arm (12, 13) to stiffen them at their pivotally connected ends during vehicle roll conditions such that the ends of said arms act as though they are fixed or at least tending to be fixed as in the arrangement of the present invention. In other words, McJunkin, because of its structure, is incapable of functioning like the present invention as claimed in claim 1.

Applicant has also attached copies of pages from two textbooks which provide definitions and examples of beams with pin-jointed ends (normal ride conditions of the leaf springs) and fixed or encastre ends (roll conditions). The first textbook reference is G. H. Ryder, *Strength of Materials* 72-73, 152-153, 178-179 (2d ed., Cleaver-Hume Press Ltd. 1958). The second textbook reference is Raymond J. Roark, *Formulas for Stress and Strain* 102-105 (3d ed., McGraw-Hill Book Company, Inc. 1954).

For these reasons, McJunkin does not teach or suggest the features of the presently claimed invention. Further, there is nothing in the teaching of Wilson which would enable one skilled in the art to overcome the aforementioned shortcomings in McJunkin when contrasted with the present invention as now claimed. Therefore, applicant respectfully requests that the Section 103(a) rejection of claim 1 over McJunkin, Jr. in view of Wilson be withdrawn.

This amendment and request for reconsideration is felt to be fully responsive to the comments and suggestions of the Examiner and to present the claims in condition for allowance. Favorable action is requested.

Respectfully submitted,

John Bolland Reast

Fildes & Outland, P.C.

Chris J. Fildes

Christopher J. Fildes, Attorney
Registration No. 32,132
20916 Mack Avenue, Suite 2
Grosse Pointe Woods, MI 48236
(313) 885-1500

STRENGTH
of
MATERIALS

By

G. H. RYDER

M.A. (Cantab), A.M.I.Mech.E.

Principal Lecturer,
Royal Military College of Science, Shrivenham.
Formerly Senior Lecturer,
College of Technology, Birmingham.

SECOND EDITION
ENLARGED

LONDON
CLEAVER-HUME PRESS LTD

Ryder's
Strengt
Ryder succ
dio—it isn't
ment and a
provides w
cate or Deg
ing demanc
fluous at t
London U
additions.
called first
for a consi
About t
first, this in
and Exper
of stress co
with refere
tice, on str
on several
other topic
knowledge
amination,
more vari
lems and r
But the
clear settir
analysis o
summaries
formulae,
lished. It u
teacher ar
what is wa
manner, it
and its pri

For press
Second la

CLEAVER-HUME PRESS LTD.,
Wright's Lane, Kensington,
London, W.8.

Demy 8vo; x + 338 pp.
285 line illustrations

First published 1953
Reprinted with amendments 1955
Second Edition 1957
Reprinted with amendments 1958

Drawings by E. L. Billington
Made and printed in Great Britain by
William Clowes and Sons Ltd, London and Beccles

Preface to the Second Edition

Extensive additions have been made to this new edition, either to bring it up to date with new developments, to improve the original presentation, or to keep up with the widening scope of examination syllabuses. The emphasis on basic principles and interpretation of the underlying physical behaviour is however maintained and extended to the new material.

There are additions on Material Testing and Experimental Methods, and the effects of stress concentrations in members under tensile, bending, and twisting loads are discussed in their relevant contexts. Extensions have been made to the elastic theory in the fields of strain analysis, with particular reference to resistance strain gauge practice; torsion of thin-walled and cellular tubes and open sections; beams on elastic foundations; and strut analysis by the energy method. Developments in the plastic yielding of steel are given prominence, with a new chapter on the Plastic Theory of Bending, and sections on the plastic yielding of shafts and of tubes under pressure.

The number and scope of illustrative examples and of problems to be worked is now considerably increased, and additional references have been given at the ends of chapters, particularly to works on the subject of a practical nature.

G. H. Ryder

March, 1957

From the Original Preface

This book sets out to cover in one volume the whole of the work required up to Final Degree standard in Strength of Materials. The only prior knowledge assumed is of elementary Applied Mechanics and Calculus. Consequently, it should prove of value to students preparing for a Higher National Certificate and Professional Institution examinations, as well as those following a Degree course. The contents are based on the Syllabus of the University of London, with certain additions.

The main aim has been to give a clear understanding of the principles underlying engineering design, and a special effort has been made to indicate the shortest analysis of each particular problem. Each chapter, starting with assumptions and theory, is complete in itself and is built

portion is clockwise, and on the right portion anticlockwise. This is referred to as *sagging* bending moment since it tends to make the beam concave upwards at AA. Negative bending moment is termed *hogging*.

A *bending moment diagram* is one which shows the variation of bending moment along the length of the beam.

Defines
team.

5.3. Types of Load. A beam is normally horizontal, the loads being vertical, other cases which occur being looked upon as exceptions.

A *concentrated* load is one which is considered to act at a point, although in practice it must really be distributed over a small area.

A *distributed* load is one which is spread in some manner over the length of the beam. The rate of loading w is quoted as "lb./ft. run" or "tons/ft. run," and may be uniform, or may vary from point to point along the beam.

5.4. Types of Support. A *simple* or *free* support is one on which the beam is rested, and which exerts a reaction on the beam. Normally the reaction will be considered as acting at a point, though it may be distributed along a length of beam in a similar manner to a distributed load.

A *built-in* or *encastré* support is frequently met with, the effect being to fix the direction of the beam at the support. In order to do this the support must exert a "fixing" moment M and a reaction R on the beam (Fig. 75). A beam thus fixed at one end is called a *cantilever*; when fixed at both ends the reactions are not statically determinate, and this case will be dealt with later (Chapter X).



Fig. 75

In practice it is not usually possible to obtain perfect fixing, and the "fixing" moment applied will be related to the angular movement at the support. When in doubt about the rigidity (e.g. a riveted joint), it is "safer" to assume that the beam is freely supported.

5.5. Relations between w, F, and M. Fig. 76 shows a short length



Fig. 76

δx imagined to be a "slice" cut out from a loaded beam at a distance x from a fixed origin O.

Let the shearing force at the section x be F, and at $x+\delta x$ be $F+\delta F$. Similarly, the bending moment is M at x, and $M+\delta M$ at $x+\delta x$. If w is the mean rate of loading on the length δx, the total load is $w\delta x$, acting approximately (exactly, if uniformly distributed) through the centre C. The element must be in equilibrium under the action of these forces and couples, and the following equations are obtained.

Taking moments about C:

$$M+F.\delta x/2+(F+\delta F)\delta x/2=M+\delta M$$

Neglecting the product $\delta F.\delta x$, and taking the limit, gives

$$F=dM/dx \qquad (1)$$

Resolving vertically

$$w\delta x+F+\delta F=F$$

or

$$w=-dF/dx \qquad (2)$$

$$=-d^2M/dx^2 \quad \text{from (1)} \qquad (3)$$

From equation (1) it can be seen that, if M is varying continuously, zero shearing force corresponds to maximum or minimum bending moment, the latter usually indicating the greatest value of negative bending moment. It will be seen later, however, that "peaks" in the bending moment diagram frequently occur at concentrated loads or reactions, and are not then given by $F=dM/dx=0$, although they may represent the greatest bending moment on the beam. Consequently it is not always sufficient to investigate the points of zero shearing force when determining the maximum bending moment.

At a point on the beam where the type of bending is changing from sagging to hogging, the bending moment must be zero, and this is called a point of *inflection* or *contraflexure*.

By integrating equation (1) between two values of $x=a$ and b, then

$$M_b-M_a=\int_a^b F dx$$

showing that the increase in bending moment between two sections is given by the area under the shearing force diagram.

Similarly, integrating equation (2)

$$F_a-F_b=\int_a^b w dx$$

= the area under the load distribution diagram.

Integrating equation (3) gives

$$M_a-M_b=\int\int_a^b w dx.dx$$

These relations prove very valuable when the rate of loading cannot

CHAPTER IX

Deflection of Beams

9.1. Strain Energy due to Bending. Consider a short length of beam δx, under the action of a bending moment M. If f is the bending stress on an element of the cross-section of area δA at a distance y from the neutral axis, the strain energy of the length δx is given by

$$\delta U = \int (f^2/2E) \times \text{volume} \quad \text{(Para. 1.9)}$$
$$= \delta x \int f^2 . dA/2E$$
$$= (\delta x/2E)\int M^2 y^2 dA/I^2$$

But $\int y^2 . dA = I$

hence $\delta U = (M^2/2EI)\delta x$

For the whole beam:

$$U = \int M^2 . dx/2EI$$

The product EI is called the ***Flexural Rigidity*** of the beam.

EXAMPLE 1. *A simply supported beam of length l carries a concentrated load W at distances of a and b from the two ends. Find expressions for the total strain energy of the beam and the deflection under the load.*

beam with pin jointed ends.

The integration for strain energy can only be applied over a length of beam for which a continuous expression for M can be obtained. This usually implies a separate integration for each section between two concentrated loads or reactions.



Fig. 141

Referring to Fig. 141, for the section AB,

$$M = (Wb/l)x$$

$$U_a = \int_0^a \frac{W^2 b^2 x^2}{2l^2 EI} . dx$$
$$= \frac{W^2 b^2}{2l^2 EI}\left[\frac{x^3}{3}\right]_0^a$$
$$= W^2 a^3 b^2 / 6EIl^2$$

Similarly, by taking a variable X measured from C

$$U_b = \int_0^b \frac{W^2 a^2 X^2}{2l^2 EI} . dX = W^2 a^2 b^3 / 6EIl^2$$

Total $U = U_a + U_b = (W^2 a^2 b^2 / 6EIl^2)(a+b)$
$= W^2 a^2 b^2 / 6EIl$

But, if δ is the deflection under the load, the strain energy must equal the work done by the load (gradually applied), i.e.

$$\tfrac{1}{2}W\delta = W^2 a^2 b^2 / 6EIl$$
$$\therefore \ \delta = Wa^2 b^2 / 3EIl$$

For a central load, $a = b = l/2$, and

$$\delta = (W/3EIl)(l^2/4)(l^2/4)$$
$$= Wl^3/48EI$$

It should be noted that this method of finding deflection is limited to cases where only one concentrated load is applied (i.e. doing work), and then only gives the deflection under the load. A more general application of strain energy to deflection is found in Castigliano's theorem (Para. 11.4).

EXAMPLE 2. *Compare the strain energy of a beam, simply supported at its ends and loaded with a uniformly distributed load, with that of the same beam centrally loaded and having the same value of maximum bending stress.* (U.L.)

If l is the span and EI the flexural rigidity, then for a uniformly distributed load w, the end reactions are $wl/2$, and at a distance x from one end

$$M = (wl/2)x - wx^2/2$$
$$= (wx/2)(l-x)$$

$$U_1 = \int_0^l \frac{w^2 x^2 (l-x)^2 dx}{4 \times 2EI}$$
$$= \frac{w^2}{8EI}\int_0^l (l^2 x^2 - 2lx^3 + x^4)dx$$
$$= (w^2 l^5 / 8EI)(\tfrac{1}{3} - \tfrac{2}{4} + \tfrac{1}{5})$$
$$= w^2 l^5 / 240EI \qquad \text{(i)}$$

For a central load of W,

$$U_2 = \tfrac{1}{2}W\delta$$
$$= W^2 l^3 / 96EI \qquad \text{(ii)}$$

see also Example 1.

Maximum bending stress $= \hat{M}/Z$, and for a given beam depends on the maximum bending moment.

Equating maximum bending moments,

$$wl^2/8 = Wl/4 \quad \text{(Chap. 5)} \qquad \text{(iii)}$$
$$\therefore \ wl = 2W$$

Ratio $U_1/U_2 = (w^2 l^5/240)(96/W^2 l^3)$ from (i) and (ii)
$= (96/240)(w^2 l^2/W^2)$
$= (96/240)4$ from (iii)
$= 8/5$

CHAPTER X

Built-In and Continuous Beams

10.1. Moment-Area Method for Built-in Beams. A beam is said to be built-in or encastre when both its ends are rigidly fixed so that the slope remains horizontal. Usually also the ends are at the same level.

It follows from the moment-area method (Para. 9.5) that, since the change of slope from end to end and the intercept x are both zero

$$\Sigma A = 0 \tag{1}$$

and

$$\Sigma A\bar{x} = 0 \tag{2}$$



Fig. 168

It will be found convenient to show the bending moment diagram due to any loading such as Fig. 168(a) as the algebraic sum of two parts, one due to the loads, treating the beam as simply supported (Fig. 168(b)), and the other due to the end moments introduced to bring the slopes back to zero (Fig. 168(c)).

The area and end reactions obtained if freely supported will be referred to as the *free moment diagram* and the *free reactions*, A_1, R_1 and R_2 respectively.

The fixing moments at the ends are M_a and M_b, and in order to maintain equilibrium when M_a and M_b are unequal, the reactions $R = (M_a - M_b)/l$ are introduced, being upwards at the left-hand end and downwards at the right-hand end. Due to M_a, M_b, and R, the bending moment at a distance x from the left-hand end

$$= -M_a + Rx = -M_a + [(M_a - M_b)/l]x.$$

This gives a straight line going from a value $-M_a$ at $x=0$ to $-M_b$ at $x=l$, and hence the *fixing moment diagram*, A_2 (Fig. 168 (d)).

For downward loads, A_1 is a positive area (sagging B.M.), and A_2 a negative area (hogging B.M.) consequently the equations (1) and (2) reduce to

$$A_1 = A_2 \tag{1}$$

and

$$A_1\bar{x}_1 = A_2\bar{x}_2 \quad \text{(numerically)} \tag{2}$$

i.e. **Area of free moment diagram = Area of fixing moment diagram**

and **Moments of areas of free and fixing diagrams are equal.**

It may be necessary to break down the areas still further to obtain convenient triangles and parabolas.

These two equations enable M_a and M_b to be found, and the total reactions at the ends are

$$R_a = R_1 + R = R_1 + (M_a - M_b)/l$$

and

$$R_b = R_2 - R = R_2 - (M_a - M_b)/l$$

Finally, the combined bending moment diagram is shown in Fig. 168(e) as the algebraic sum of the two components.

EXAMPLE 1. *Obtain expressions for the maximum bending moment and deflection of a beam of length l and flexural rigidity EI, fixed horizontally at both ends, carrying a load W (a) concentrated at mid-span, (b) uniformly distributed over the whole beam.*



Fig. 169

beams
with
fixed
moment,
and

(a) By symmetry $M_a = M_b = M$, say (Fig. 169).

The free moment diagram is a triangle with maximum ordinate $Wl/4$ (Chap. V).

$\therefore$ Area $A_1 = \frac{1}{2}(Wl/4)l = Wl^2/8$

Area $A_2 = Ml$

Equating $A_1 = A_2$ from (1), gives

$$M = Wl/8$$

The combined bending moment diagram is therefore as shown in the lower diagram, Fig. 169, and the maximum bending moment is $Wl/8$, occurring at the end (hogging), and the centre (sagging).

Other McGraw-Hill INTERNATIONAL STUDENT EDITIONS in Related Fields

CHOW: Open Channel Hydraulics
DAUGHERTY: Fluid Mechanics, 5th Ed.
DAVIS: Handbook of Applied Hydraulics, 2nd Ed.
DAVIS: Surveying, 4th Ed.
DUNHAM: Theory and Practice of Reinforced Concrete, 3rd Ed.
DUNHAM: Foundations of Structures, 2nd Ed.
EHLERS: Municipal and Rural Sanitation, 5th Ed.
FRENCH: A Manual of Engineering Drawing for Students and Draftsmen, 9th Ed.
FRENCH: Mechanical Drawing, 6th Ed.
GAYLORD: Design of Steel Structures
HAMMING: Numerical Methods For Scientists And Engineers
HOOL: Steel and Timber Structures, 2nd Ed.
JENSEN: Applied Engineering Mechanics, 2nd Ed.
LASS: Vector and Tensor Analysis
LINSLEY: Applied Hydrology
MOORE: Textbook of the Materials of Engineering, 8th Ed.
NORRIS: Elementary Structural Analysis, 2nd Ed.
PEURIFOY: Construction Planning, Equipment, and Methods
PIPES: Applied Mathematics for Engineers and Physicists, 2nd Ed.
SOKOLNIKOFF: Mathematics of Physics and Modern Engineering
STEEL: Water Supply and Sewerage, 4th Ed.
STREETER: Fluid Mechanics, 3rd Ed.
SYNGE: Principles of Mechanics, 3rd Ed.
TIMOSHENKO: Engineering Mechanics, 4th Ed.
TIMOSHENKO: Theory of Elastic Stability, 2nd Ed.
TIMOSHENKO: Theory of Elasticity, 2nd Ed.
TIMOSHENKO: Theory of Plates and Shells, 2nd Ed.
TSCHEBOTARIOFF: Soil Mechanics, Foundations, and Earth Structures
WANG: Statistically Indeterminate Structures
WYLIE: Advanced Engineering Mathematics

formulas for STRESS & STRAIN

McGRAW-HILL
KŌGAKUSHA

International Student Edition

Third Edition

formulas for STRESS & STRAIN

R. J. Roark

This is the stress engineers bible
and is often offered in electronic form
in CAD software – eg MathCAD.

FORMULAS
for
STRESS AND STRAIN

RAYMOND J. ROARK
Professor of Mechanics, The University of Wisconsin

THIRD EDITION

INTERNATIONAL STUDENT EDITION

McGRAW-HILL BOOK COMPANY, INC.
NEW YORK TORONTO LONDON
KŌGAKUSHA COMPANY, LTD.
TOKYO

FORMULAS FOR STRESS AND STRAIN

INTERNATIONAL STUDENT EDITION

Exclusive rights by Kōgakusha Co., Ltd. for manufacture and export from Japan. This book cannot be re-exported from the country to which it is consigned by Kōgakusha Co., Ltd. or by McGraw-Hill Book Company, Inc. or any of its subsidiaries.

I

Library of Congress Catalog Card Number: 53-5175

TOKYO PRINTING CO., LTD., TOKYO, JAPAN

PREFACE TO THE THIRD EDITION

As in the first revision, new data have been added, and tables of formulas and coefficients have been amplified. Some of the more important changes are as follows:

In Chap. 8 (Beams) the discussion of shear lag has been rewritten to include the results of recent investigations, and in Table VIII formulas for circular arches have been added. In Chap. 10 (Flat Plates) the table of stress and deflection coefficients has been expanded to cover a number of additional cases and to include coefficients for edge slope; also a table of coefficients for rectangular plates with large deflection has been added. In Chap. 11 (Columns) Table XI has been revised to bring it in line with current specifications. In Chap. 12 (Pressure Vessels) Table XIII has been extensively revised and amplified, and the former example of stress calculation for thin vessels has been replaced by one that illustrates the use of the new formulas and provides comparison with experimental results. Table XVII (Factors of Stress Concentration) has been extended to include factors based on the important work of Neuber.

In addition, miscellaneous formulas and data believed to be of value have been introduced in appropriate chapters, and the reference lists have been revised and extended.

The literature pertaining to applied mechanics and elasticity has grown to such proportions that it is manifestly impossible to include more than a small fraction of it in a single volume, even by reference. Those working in the field will of course be familiar with the important sources of published material; others will be able to gain some idea of where to seek additional information from the references given in this book and from the available bibliographies and digests, particularly from "Applied Mechanics Reviews," published monthly by the American Society of Mechanical Engineers, and from the "Technical Data Digest," published by the Central Air Documents Office.

Again the author wishes to thank the many readers to whom he is indebted for suggestions and for help in detecting errors and omissions. In particular he wishes to make grateful acknowledgment to Prof. Eric Reissner of the Massachusetts Institute of

11 = Symmetrical spring under normal deflection.

TABLE III.—SHEAR, MOMENT, AND DEFLECTION FORMULAS FOR BEAMS.—(Continued)

Loading, support, and reference number	Reactions R_1 and R_2, vertical shear V	Bending moment M and maximum bending moment	Deflection y, maximum deflection, and end slope θ
9. Cantilever, end couple 	$R_1 = 0$ $V = 0$	$M = M_0$ Max $M = M_0$ (A to B)	$y = \frac{1}{2}\frac{M_0}{EI}(l^2 - 2lx + x^2)$ Max $y = +\frac{1}{2}\frac{M_0 l^2}{EI}$ at A $\theta = -\frac{M_0 l}{EI}$ at A
10. Cantilever, intermediate couple 	$R_1 = 0$ $V = 0$	(A to B) $M = 0$ (B to C) $M = M_0$ Max $M = M_0$ (B to C)	(A to B) $y = -\frac{M_0 a}{EI}\left(l - \frac{1}{2}a - x\right)$ (B to C) $y = \frac{1}{2}\frac{M_0}{EI}[(x - l + a)^2 - 2a(x - l + a) + a^2]$ Max $y = -\frac{M_0 a}{EI}\left(l - \frac{1}{2}a\right)$ at A $\theta = -\frac{M_0 a}{EI}$ (A to B)
11. End supports, center load 	$R_1 = +\frac{1}{2}W$ $R_2 = +\frac{1}{2}W$ (A to B) $V = +\frac{1}{2}W$ (B to C) $V = -\frac{1}{2}W$	(A to B) $M = +\frac{1}{2}Wx$ (B to C) $M = +\frac{1}{2}W(l - x)$ Max $M = +\frac{1}{4}Wl$ at B	(A to B) $y = -\frac{1}{48}\frac{W}{EI}(3l^2x - 4x^3)$ Max $y = -\frac{1}{48}\frac{Wl^3}{EI}$ at B $\theta = -\frac{1}{16}\frac{Wl^2}{EI}$ at A, $\theta = +\frac{1}{16}\frac{Wl^2}{EI}$ at C
12. End supports, intermediate load 	$R_1 = +W\frac{b}{l}$ $R_2 = +W\frac{a}{l}$ (A to B) $V = +W\frac{b}{l}$ (B to C) $V = -W\frac{a}{l}$	(A to B) $M = +W\frac{b}{l}x$ (B to C) $M = +W\frac{a}{l}(l - x)$ Max $M = +W\frac{ab}{l}$ at B	(A to B) $y = -\frac{Wbx}{6EIl}[2l(l - x) - b^2 - (l - x)^2]$ (B to C) $y = -\frac{Wa(l - x)}{6EIl}[2lb - b^2 - (l - x)^2]$ Max $y = -\frac{Wab}{27EIl}(a + 2b)\sqrt{3a(a + 2b)}$ at $x = \sqrt{\frac{1}{3}a(a + 2b)}$ when $a > b$ $\theta = -\frac{1}{6}\frac{W}{EI}\left(bl - \frac{b^3}{l}\right)$ at A; $\theta = +\frac{1}{6}\frac{W}{EI}\left(2bl + \frac{b^3}{l} - 3b^2\right)$ at C
13. End supports, uniform load 	$R_1 = +\frac{1}{2}W$ $R_2 = +\frac{1}{2}W$ $V = \frac{1}{2}W\left(1 - \frac{2x}{l}\right)$	$M = \frac{1}{2}W\left(x - \frac{x^2}{l}\right)$ Max $M = +\frac{1}{8}Wl$ at $x = \frac{1}{2}l$	$y = -\frac{1}{24}\frac{Wx}{EIl}(l^3 - 2lx^2 + x^3)$ Max $y = -\frac{5}{384}\frac{Wl^3}{EI}$ at $x = \frac{1}{2}l$ $\theta = -\frac{1}{24}\frac{Wl^2}{EI}$ at A $\theta = +\frac{1}{24}\frac{Wl^2}{EI}$ at B

14. End supports, partial uniform load 	$R_1 = W\frac{d}{l}$ $R_2 = \frac{W}{l}\left(c + \frac{1}{2}a\right)$ (A to B) $V = R_1$ (B to C) $V = R_1 - W\frac{x - c}{a}$ (C to D) $V = R_1 - W$	(A to B) $M = R_1x$ (B to C) $M = R_1x - W\frac{(x - c)^2}{2a}$ (C to D) $M = R_1x - W(x - \frac{1}{2}a - \frac{1}{2}b)$ Max $M = W\frac{d}{l}\left(c + \frac{ad}{2l}\right)$ at $x = c + \frac{ad}{l}$	(A to B) $y = \frac{1}{48EI}\left\{8R_1(x^3 - l^2x) + Wx\left[\frac{8b^3}{l} - \frac{2ba^2}{l} + \frac{a^3}{l} + 2a^2\right]\right\}$ (B to C) $y = \frac{1}{48EI}\left\{8R_1(x^3 - l^2x) + Wx\left[\frac{8b^3}{l} - \frac{2ba^2}{l} + \frac{a^3}{l} + 2a^2\right] - 2W\frac{(x - c)^4}{a}\right\}$ (C to D) $y = \frac{1}{48EI}\left\{8R_2(x^3 - l^2x) + Wx\left[\frac{8b^3}{l} - \frac{2ba^2}{l} + \frac{a^3}{l}\right] - 8W(x - \frac{1}{2}a - \frac{1}{2}b)^3 + W(2ba^2 - a^3)\right\}$ $\theta = \frac{1}{48EI}\left[-8R_1l^2 + W\left(\frac{8b^3}{l} - \frac{2ba^2}{l} + \frac{a^3}{l} + 2a^2\right)\right]$ at A; $\theta = \frac{1}{48EI}\left[16R_1l^2 - W\left(24d^2 - \frac{8b^3}{l} + \frac{2ba^2}{l} - \frac{a^3}{l}\right)\right]$ at B
15. End supports, triangular load 	$R_1 = \frac{1}{3}W$ $R_2 = \frac{2}{3}W$ $V = W\left(\frac{1}{3} - \frac{x^2}{l^2}\right)$	$M = \frac{1}{3}W\left(x - \frac{x^3}{l^2}\right)$ Max $M = 0.128Wl$ at $x = l\left(\frac{\sqrt{3}}{3}\right) = 0.5774l$	$y = -\frac{1}{180}\frac{Wx}{EIl^2}(3x^4 - 10l^2x^2 + 7l^4)$ Max $y = -0.01304\frac{Wl^3}{EI}$ at $x = 0.5193l$ $\theta = -\frac{7}{180}\frac{Wl^2}{EI}$ at A; $\theta = +\frac{8}{180}\frac{Wl^2}{EI}$ at B
16. End supports, partial triangular load 	$R_1 = W\frac{d}{l}$ $R_2 = W\frac{l - d}{l}$ (A to B) $V = +R_1$ (B to C) $V = R_1 - \left(\frac{x - c}{a}\right)^2 W$ (C to D) $V = R_1 - W$	(A to B) $M = R_1x$ (B to C) $M = R_1x - W\frac{(x - c)^3}{3a^2}$ (C to D) $M = R_1x - \frac{1}{3}W(3x - c - 2b)$ Max $M = W\frac{d}{l}\left(c + \frac{2}{3}a\sqrt{\frac{d}{l}}\right)$ at $x = c + a\sqrt{\frac{d}{l}}$	(A to B) $y = \frac{1}{6EI}\left\{R_1(x^3 - l^2x) + Wx\left[\frac{d^3}{l} + \frac{1}{6}a^2\left(1 - \frac{d}{l}\right) + \frac{17}{270}\frac{a^3}{l}\right]\right\}$ (B to C) $y = \frac{1}{6EI}\left[R_1(x^3 - l^2x) - \frac{1}{10}W\frac{(x - c)^5}{a^2} + Wx\left(\frac{d^3}{l} + \frac{1}{6}a^2 - \frac{1}{6}a^2\frac{d}{l} + \frac{17}{270}\frac{a^3}{l}\right)\right]$ (C to D) $y = \frac{1}{6EI}\left\{R_1(x^3 - l^2x) - W\left[\left(x - \frac{1}{3}a - \frac{2}{3}b\right)^3 - x\frac{d^3}{l} - \frac{1}{6}a^2\left(1 - \frac{x}{l}\right) + \frac{17}{270}a^3\left(1 - \frac{x}{l}\right)\right]\right\}$ $\theta = \frac{1}{6EI}\left[-R_1l^2 + W\left(\frac{d^3}{l} + \frac{1}{6}a^2 + \frac{17}{270}\frac{a^3}{l} - \frac{1}{6}\frac{a^2d}{l}\right)\right]$ at A $\theta = \frac{1}{6EI}\left[2R_1l^2 + W\left(\frac{d^3}{l} + \frac{17}{270}\frac{a^3}{l} - \frac{1}{6}\frac{a^2d}{l} - 3d^2\right)\right]$ at D

TABLE III.—SHEAR, MOMENT, AND DEFLECTION FORMULAS FOR BEAMS.—(*Continued*)

Loading, support, and reference number	Reactions R_1 and R_2, vertical shear V	Bending moment M and maximum bending moment	Deflection y, maximum deflection, and end slope θ
17. End supports, triangular load 	$R_1 = \frac{1}{2}W$ $R_2 = \frac{1}{2}W$ (A to B) $V = \frac{1}{2}W\left(1 - \frac{4x^2}{l^2}\right)$ (B to C) $V = -\frac{1}{2}W\left(1 - 4\frac{(l-x)^2}{l^2}\right)$	(A to B) $M = \frac{1}{2}W\left(x - \frac{4x^3}{3l^2}\right)$ (B to C) $M = \frac{1}{2}W\left[(l - x) - \frac{4(l-x)^3}{3l^2}\right]$ Max $M = \frac{1}{6}Wl$ at B	(A to B) $y = \frac{1}{6}\frac{Wx}{EIl^2}$ [illegible] Max $y = -\frac{1}{60}\frac{Wl^3}{EI}$ at B $\theta = -\frac{5}{96}\frac{Wl^2}{EI}$ at A; $\theta = +\frac{5}{96}\frac{Wl^2}{EI}$ at C
18. End supports, triangular load 	$R_1 = \frac{1}{2}W$ $R_2 = \frac{1}{2}W$ (A to B) $V = \frac{1}{2}W\left(\frac{l-2x}{l}\right)^2$ (B to C) $V = -\frac{1}{2}W\left(\frac{2x-l}{l}\right)^2$	(A to B) $M = \frac{1}{2}W\left(x - 2\frac{x^2}{l} + \frac{4}{3}\frac{x^3}{l^2}\right)$ (B to C) $M = \frac{1}{2}W\left[(l-x) - 2\frac{(l-x)^2}{l} + \frac{4}{3}\frac{(l-x)^3}{l^2}\right]$ Max $M = \frac{1}{12}Wl$ at B	(A to B) $y = \frac{1}{12}\frac{W}{EI}\left(x^3 - \frac{x^4}{l} + \frac{2}{5}\frac{x^5}{l^2} - \frac{3}{8}l^2x\right)$ Max $y = -\frac{3}{320}\frac{Wl^3}{EI}$ at B $\theta = -\frac{1}{32}\frac{Wl^2}{EI}$ at A; $\theta = +\frac{1}{32}\frac{Wl^2}{EI}$ at B
19. End supports, end couple 	$R_1 = -\frac{M_0}{l}$ $R_2 = +\frac{M_0}{l}$ $V = R_1$	$M = M_0 + R_1x$ Max $M = M_0$ at A	$y = \frac{1}{6}\frac{M_0}{EI}\left(3x^2 - \frac{x^3}{l} - 2lx\right)$ Max $y = -0.0642\frac{M_0l^2}{EI}$ at $x = 0.422l$ $\theta = -\frac{1}{3}\frac{M_0l}{EI}$ at A $\theta = +\frac{1}{6}\frac{M_0l}{EI}$ at B
20. End supports, intermediate couple 	$R_1 = -\frac{M_0}{l}$ $R_2 = +\frac{M_0}{l}$ (A to C) $V = R_1$	(A to B) $M = R_1x$ (B to C) $M = R_1x + M_0$ Max $-M = R_1a$ just left of B Max $+M = R_1a + M_0$ just right of B	(A to B) $y = \frac{1}{6}\frac{M_0}{EI}\left[\left(6a - 3\frac{a^2}{l} - 2l\right)x - \frac{x^3}{l}\right]$ (B to C) $y = \frac{1}{6}\frac{M_0}{EI}\left[3a^2 + 3x^2 - \frac{x^3}{l} - \left(2l + 3\frac{a^2}{l}\right)x\right]$ $\theta = -\frac{1}{6}\frac{M_0}{EI}\left(2l - 6a + 3\frac{a^2}{l}\right)$ at A; $\theta = +\frac{1}{6}\frac{M_0}{EI}\left(l - 3\frac{a^2}{l}\right)$ at C $\theta = \frac{M_0}{EI}\left(a - \frac{a^2}{l} - \frac{l}{3}\right)$ at B

21. Same spring in roll with stab. bar fixing one end.

TABLE III.—SHEAR, MOMENT, AND DEFLECTION FORMULAS FOR BEAMS.—(*Continued*)
Statically Indeterminate Cases

Loading, support, and reference number	Reactions R_1 and R_2, constraining moments M_1 and M_2, and vertical shear V	Bending moment M and maximum positive and negative bending moments	Deflection y, maximum deflection, and end slope θ
21. One end fixed, one end supported. Center load 	$R_1 = \frac{5}{16}W$ $R_2 = \frac{11}{16}W$ $M_2 = \frac{3}{16}Wl$ (A to B) $V = +\frac{5}{16}W$ (B to C) $V = -\frac{11}{16}W$	(A to B) $M = \frac{5}{16}Wx$ (B to C) $M = W(\frac{1}{2}l - \frac{11}{16}x)$ Max $+M = \frac{5}{32}Wl$ at B Max $-M = -\frac{3}{16}Wl$ at C	(A to B) $y = \frac{1}{96}\frac{W}{EI}(5x^3 - 3l^2x)$ (B to C) $y = \frac{1}{96}\frac{W}{EI}\left[5x^3 - 16\left(x - \frac{l}{2}\right)^3 - 3l^2x\right]$ Max $y = -0.00932\frac{Wl^3}{EI}$ at $x = 0.4472l$ deflection $\theta = -\frac{1}{32}\frac{Wl^2}{EI}$ at A
22. One end fixed, one end supported. Intermediate load 	$R_1 = \frac{1}{2}W\left(\frac{3a^2l - a^3}{l^3}\right)$ $R_2 = W - R_1$ $M_2 = \frac{1}{2}W\left(\frac{a^3 + 2al^2 - 3a^2l}{l^2}\right)$ (A to B) $V = +R_1$ (B to C) $V = R_1 - W$	(A to B) $M = R_1x$ (B to C) $M = R_1x - W(x - l + a)$ Max $+M = R_1(l - a)$ at B; max possible value $= 0.174Wl$ when $a = 0.634l$ Max $-M = -M_2$ at C; max possible value $= -0.1927Wl$ when $a = 0.4227l$	(A to B) $y = \frac{1}{6EI}[R_1(x^3 - 3l^2x) + 3Wa^2x]$ (B to C) $y = \frac{1}{6EI}[R_1(x^3 - 3l^2x) + W[3a^2x - (x - b)^3]]$ If $a < 0.586l$, max y is between A and B at: $x = l\sqrt{1 - \frac{2l}{3l - a}}$ If $a > 0.586l$, max y is at: $x = \frac{l(l^2 + b^2)}{3l^2 - b^2}$ If $a = 0.586l$, max y is at B and $= -0.0098\frac{Wl^3}{EI}$, max possible deflection $\theta = \frac{1}{4}\frac{W}{EI}\left(\frac{a^3}{l} - a^2\right)$ at A
23. One end fixed, one end supported. Uniform load 	$R_1 = \frac{3}{8}W$ $R_2 = \frac{5}{8}W$ $M_2 = \frac{1}{8}Wl$ $V = W\left(\frac{3}{8} - \frac{x}{l}\right)$	$M = W\left(\frac{3}{8}x - \frac{1}{2}\frac{x^2}{l}\right)$ Max $+M = \frac{9}{128}Wl$ at $x = \frac{3}{8}l$ Max $-M = -\frac{1}{8}Wl$ at B	$y = \frac{1}{48}\frac{W}{EIl}(3lx^3 - 2x^4 - l^3x)$ Max $y = -0.0054\frac{Wl^3}{EI}$ at $x = 0.4215l$ $\theta = -\frac{1}{48}\frac{Wl^2}{EI}$ at A

As can be seen defl^n. of 21 = 0·00932 × constant
against 11 = 1/48 = ·0208 × "

∴ 11 deflects much more ∴ 21 is stiffer.
by 2·08 .... = 2·235 ti..

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: ______________________________

IMAGES ARE BEST AVAILABLE COPY.
As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.